



CARACTERISTICI CONSTRUCTIVE / DESIGN CHARACTERISTICS :

- constructie / design : SR ISO 10631
- lungimi de constructie / overall length : EN 558-1-S14 ;ISO 5752-S14
- flanse de legatura / flange connection : EN 1092-2; ISO 7005-2 ; DIN 2501

(dimensiuni in mm / dimension in mm)

DN	Tip reductor Gear-box type	A	B	C	d1	d2	nxd3	E	F	H	L	Dr	Numar rot/ cursa Rot/ stroke	Moment actionare roata Driving torque on wheel ≈[daNm]	Masa neta Net weight ≈ [Kg]	
200	RW50-32	445	232	77	340	295	8x23	65	-	163	230	250	12,5	6,5	60	
250		505	280		400	350	12x23				250				74	
300	RW65-40	558	315	100	455	400	16x23	80	-	223	270	300	11	10,5	106	
350		624	345		520	460					16x23				290	143
400		670	378		580	515					16x28				310	152
450	RW90-58	784	386	110	640	565	20x28	100	-	255	330	400	16,25	12,8	187	
500		779	398		715	620					20x28				350	221
600	RW120-64	843	445	130	840	725	20x31	130	-	270	390	500	56.5	20,5	370	
700	RW150+RS105- 252	1126	576	133	910	840	24x30	-	302	433	430	500	62.5	16,3	584	
800		1340	670		1025	950	24x33				470				759	
900	Q20D11	1464	725	150	1125	1050	28x33	-	353	455	510	500	106.25		1035	

Pentru confirmare va rugam folositi fisa tehnica contractuala / For confirmation, please use the technical sheet of agreement FTC9